





版板所有为：深圳市鑫南天科技有限公司，网址：<http://www.szxnt.com>


\* ROHS COMPLIANT



MECHANICAL:



RECOMMENDED  
PANEL CUTOUT DIMENSION



P, C, B RECOMMENDED HOLE LAYOUT SEEN FROM COMPONENT SIDE.  
ALL CENTRELINE DIMENSIONS ARE BASIC

Metal Shell : Copper Alloy, Finish: 30u" Nickel  
 Housing :Thermoplastic,PBT,UL 94V-0,Black  
 Insert :Thermoplastic,PBT,UL 94V-0,Black  
 Contact Terminal/phosphor Bronze  
 6u" Gold on Contact Area, 100u" Trm on Solder,  
 Both over 50u" Nickel Under-Plated  
 Coil Base :Phenolic,PBT,UL 94V-0,Black  
 Terminal/Copper Alloy T=0.40X0.40mm Thickness

Meets or exceeds IEEE 802.3 standard for 10/100 Base-TX  
 350uH minimum OCL with 8mA Bias current  
 Available with or without LEDs  
 Minimum 1500Vrms isolation per IEEE802.3 requirement  
 Operating temperature 0°C to +70°C  
 Storage temperature -40°C to +85°C



深圳市鑫南天科技有限公司  
 Shenzhen Xi nNanTian Technology Co., Ltd

DIMENSIONS INT:	mm
UNLESS OTHERWISE SPECIFIABLE	
DIMENSION	TOLERANCE
X.X: ±	0.38
X.XX: ±	0.25
X.XXX: ±	0.10
ANGULAR: ±	1°

PRODUCT NAME :	RJ45 Connector With Transformer	DRAWING:	COCO	DATE:	2014/01/15
PRODUCT NO. :	100Base Tab-down 1x1 Port	CHECK:	AG	DATE:	2014/01/15
DRAWING NO. :	XNT-026	APPROVED:	JEFF	DATE:	2014/01/15
SCALE:	NA	DWG ID:	P D	REV.:	A
				PAGE:	1 of 1

REVISION NO.	ECR NO.	DESCRIPTION	MARK	DATE
1				
2				