



NOTES:

- Electrical
 - .Rated Current & Voltage : DC 12 V ; 1 A
 - .Contact Resistance: 30 mohm maximum at Working Height(Quiescence)
- Environmental
 - .Operating Temperature: -25°C~+85°C
 - .Humidity Range: 10%RH~90%RH
 - .Salt Spray: 60 Hours
- .RoHs&HF compliant product.

4		1		
3	Pin	1	Contact Au 10u" Plated	
2	Magnet	1	N52 80~180u" Ni	
1	Housing	1	PA4T UL 94V-0, Black	
No.	P/NAME	QTY	Material Specification	P/N

xnt_sales@126.com
Charles 13537438849

XinNanTian Industry Co.,LTD

GENERAL TOLERANCES UNLESS SPECIFIED		TITLE	
.x ± 0.10	X. ± 5°	5pin Female Magnet Connector	
.xx ± 0.05	X. ± 3°	DRAWING NO.	
.xxx ± 0.03	X. ± 1°	XNT-005MF-05A	
SIZE	UNITS	THIRD ANGLE PROJECTION	SHEET
A4	mm[inch]		1 / 1
		APPROVED BY	REV
		ROY.WEI	B.0
		CHECKED BY	Date
		JERRY	2019/06/11
		DRAWN BY	
		LUCX	