



REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		

Specifications

- 1.Current Rating:3Amps
- 2.Insulation Resistance:1000 MΩ min.
- 3.Dielectric withstanding Voltage: AC 500V
- 4.Contact Resistance:30 mΩ max.
- 5.Operating Temperature:-25? to+85?
- 6.Contact Material: Brass
- 7.Insulation Material:Asfollows
- 8.Plated: Asfollows

Ordering Information

L208 XX -XX 0 X XX X

塑胶高度H*W
01=1.5*5.0
02=2.0*5.0
03=2.54*5.0

PIN数
1-40P

- | | | |
|--------|----------|------|
| 1、PBT | 0、Au0.8" | A、袋装 |
| 2、NV6T | 1、Au1" | B、管装 |
| 3、NV6T | 2、Au1.5" | C、盘装 |
| 4、LCP | 3、Au2" | D、卷装 |
| 5、NV66 | 4、Au3" | |
| 6、 | 5、Au5" | |
| 7、NV46 | 6、Au10" | |
| 8、NV9T | 7、半金锡 | |
| | 8、镀亮锡 | |
| | 9、镀雾锡 | |



深圳市鑫南天科技有限公司
Shenzhen Xinnantian Technology Co., Ltd

TOLERANCE UNLESS OTHERWISE SPECIFIED	TITLE	DRAWN BY	WZG	16.08.04
LINER ANGLES	PART NO	CHECKED BY		
0 ±0.30 0.° ±3°	XN-L208XXXX01XXXX	APPROVED BY		
.00 ±0.20 0.° ±2°	DRAWING NO			
.000 ±0.10 .00° ±1°	SCALE	UNITS	PAGE	SIZE
	1:1	mm	1/1	A4